

### **Certificate of Product Approval**

Certificate Number: 539c Issue: 01



### **Hosiden Besson Limited**

12 St Joseph's Close Trading Estate St Joseph's Close Hove East Sussex BN3 7EZ United Kingdom

s authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirement(s) of the standards as detailed below:

#### **Products**

#### **Alarm Warning Devices**

Banshee Excel Bi-Polar Banshee Excel Lite LED Banshee Excel Lite

#### **Standards**

EN 54-3:2001 +A1:2002 +A2:2006

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

Signed for LPCB

P Halligan Verifier 10 February 2017
Date of Issue

10 February 2017

Date of First Issue





This certificate and appendix remain the property of BRE Global Ltd and are issued subject to terms and conditions (for details visit  $\underline{www.redbooklive.com/terms}$ ).

To check the validity of this certificate and appendix please visit  $\underline{www.redbooklive.com/check}, scan the QR tag or contact us.$ 

LPCB is part of BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com







# Appendix to Certificate No: 539c Hosiden Besson Limited

Certified Product	Description	LPCB Ref.No.
Banshee Excel	Banshee Excel Audible Warning Device Notes:  1. Type A with Shallow Base, Type B with Deep Base 2. Meets the requirements of EN 54-3:2001 with the following tones: - Tone A, Banshee Fast Sweep LF, 800Hz to 950Hz @ 9Hz - Tone B, Medium Sweep LF, 800Hz to 970Hz @ 1Hz - Tone C, Slow Whoop, 500Hz rising to 1200Hz over 3.5s, silence 0.5s - Tone D, DIN Tone (DK), 1200Hz falling to 500Hz over 1s, silence 10ms - Tone E, French Fire Sounder, 554Hz for 100ms and 440Hz for 400ms	539c/01
Banshee Excel Bi-Polar	Banshee Excel Audible Warning Device  Notes:  1. Approved to Type A Indoor only with Shallow Base 2. Meets the requirements of EN 54-3:2001 with the following tones: - Tone A, Banshee Fast Sweep LF, 800Hz to 950Hz @ 9Hz - Tone B, Medium Sweep LF, 800Hz to 970Hz @ 1Hz - Tone C, Slow Whoop, 500Hz rising to 1200Hz over 3.5s, silence 0.5s - Tone D, DIN Tone (DK), 1200Hz falling to 500Hz over 1s, silence 10ms - Tone E, French Fire Sounder, 554Hz for 100ms and 440Hz for 400ms	539c/02
Banshee Excel Lite	Banshee Excel Lite Xenon Audible Warning Device Notes:  1. Type A with Shallow Base, Type B with Deep Base 2. Meets the requirements of EN 54-3:2001 with the following tones: - Tone A, Banshee Fast Sweep LF, 800Hz to 950Hz @ 9Hz - Tone B, Medium Sweep LF, 800Hz to 970Hz @ 1Hz - Tone C, Slow Whoop, 500Hz rising to 1200Hz over 3.5s, silence 0.5s - Tone D, DIN Tone (DK), 1200Hz falling to 500Hz over 1s, silence 10ms - Tone E, French Fire Sounder, 554Hz for 100ms and 440Hz for 400ms	539c/03

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

Signed for LDCP

P Halligan

10 February 2017

10 February 2017

Date of First Issue

L DCD



This certificate and appendix remain the property of BRE Global Ltd and are issued subject to terms and conditions (for details visit <a href="https://www.redbooklive.com/terms">www.redbooklive.com/terms</a>).

To check the validity of this certificate and appendix please visit <a href="https://www.redbooklive.com/check">www.redbooklive.com/check</a>, scan the QR tag or contact us.

LPCB is part of BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: <u>enquiries@breglobal.com</u>





Issue: 01



# Appendix to Certificate No: 539c Hosiden Besson Limited

Certified Product	Description	LPCB Ref.No.
LED Banshee Excel Lite	Banshee Excel Lite LED Audible Warning Device Notes:  1. Type A with Shallow Base, Type B with Deep Base 2. Meets the requirements of EN 54-3:2001 with the following tones: - Tone A, Banshee Fast Sweep LF, 800Hz to 950Hz @ 9Hz - Tone B, Medium Sweep LF, 800Hz to 970Hz @ 1Hz - Tone C, Slow Whoop, 500Hz rising to 1200Hz over 3.5s, silence 0.5s - Tone D, DIN Tone (DK), 1200Hz falling to 500Hz over 1s, silence 10ms - Tone E, French Fire Sounder, 554Hz for 100ms and 440Hz for 400ms	539c/04

#### **Bases**

Shallow Base Deep Base

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

Signed for LPCB

P Halligan

10 February 2017

10 February 2017

Date of First Issue

\_\_\_\_\_



This certificate and appendix remain the property of BRE Global Ltd and are issued subject to terms and conditions (for details visit  $\underline{www.redbooklive.com/terms}$ ).

To check the validity of this certificate and appendix please visit <a href="https://www.redbooklive.com/check">www.redbooklive.com/check</a>, scan the QR tag or contact us.

LPCB is part of BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com





Issue: 01